

PLUGGABLE TERMINAL BLOCK POWER SUPPLY



Parameter	Rated Value	Absolute Maximum												
Input Voltage	100 ~ 240 VAC	90 ~ 264 VAC												
Input Frequency	50/60 Hz	47 ~ 63 Hz												
Input Current (@100-240 VAC)	-	1.5 A												
Inrush Current (@100-240 VAC)	-	60 A												
Output Voltage	24	24 VDC ± 5%												
Output Current	0 ~ 2.0 A	-												
Overshoot	-	15%												
Certification	IEC 62368-1, UL62368-1, CSA C22.2 No.62368-1, EN62368-1, AS/NZS 62368.1, GB4943.1, BS EN IEC 62368-1													
Short-Circuit Protection	√													
Input Protection	Fuse													
HIPOT (Dielectric Withstand Test)	3000 VAC													
MTBF	20000 h													
Input Plug&Part Number	<table border="1"> <thead> <tr> <th>Global</th> <th>UK</th> <th>US</th> <th>CN</th> <th>AU</th> <th>EU</th> </tr> </thead> <tbody> <tr> <td>S011070</td> <td>S011069</td> <td>S011068</td> <td>S011067</td> <td>S011066</td> <td>S011065</td> </tr> </tbody> </table>	Global	UK	US	CN	AU	EU	S011070	S011069	S011068	S011067	S011066	S011065	<p><i>*Note: The UK plug, US plug, AU plug, EU plug and CN plug are all included in Global version.</i></p>
Global	UK	US	CN	AU	EU									
S011070	S011069	S011068	S011067	S011066	S011065									
Output Connector	Pluggable terminal block, 2-pin, 3.5 mm pitch with lock													
Related Products	EV8100, EG5200, MG460													

