

PLUGGABLE TERMINAL BLOCK POWER SUPPLY



Parameter	Rated Value	Absolute Maximum												
Input Voltage	100 ~ 240 VAC	90 ~ 264 VAC												
Input Frequency	50/60 Hz	47 ~ 63 Hz												
Input Current(@100-240 VAC)	-	0.4 A												
Inrush Current(@100-240 VAC)	-	60 A												
Output Voltage	12 VDC	12 VDC ± 5%												
Output Current	0 - 1.5 A	-												
Overshoot	-	10%												
Certification	IEC 62368 - 1:2014 (Second Edition)													
Short-Circuit Protection	√													
Input Protection	Fuse													
HIPOT (Dielectric Withstand Test)	3000 VAC													
MTBF	50000 h													
Input Plug&Part Number	<table border="1"> <thead> <tr> <th>Global*</th> <th>UK</th> <th>US</th> <th>CN</th> <th>AU</th> <th>EU</th> </tr> </thead> <tbody> <tr> <td>S011043</td> <td>S011044</td> <td>S011045</td> <td>S011046</td> <td>S011047</td> <td>S011048</td> </tr> </tbody> </table>	Global*	UK	US	CN	AU	EU	S011043	S011044	S011045	S011046	S011047	S011048	<p><i>*Note: The UK plug, US plug, AU plug, and EU plug are all included in Global version.</i></p>
Global*	UK	US	CN	AU	EU									
S011043	S011044	S011045	S011046	S011047	S011048									
Output Connector	Pluggable terminal block, 3-pin, 3.5 mm pitch with lock													
Related Products	R2110, R5020													

