

2-PIN CORD END TERMINAL POWER SUPPLY 18W



Parameter	Rated Value	Absolute Maximum												
Input Voltage	100 ~ 240 VAC	90 ~ 264 VAC												
Input Frequency	50/60 Hz	47 ~ 63 Hz												
Input Current (@100-240 VAC)	-	1.0A												
Inrush Current (@100-240 VAC)	-	80A												
Output Voltage	12 VDC	12 VDC ± 5%												
Output Current	0 ~ 1.5A	-												
Overshoot	-	10%												
Certification	IEC 62368-1:2014 (Second Edition)													
Short-Circuit Protection	√													
Input Protection	Fuse													
HIPOT (Dielectric Withstand Test)	3000 VAC													
MTBF	50000 h													
Input Plug&Part Number	<table border="1"> <thead> <tr> <th>Global*</th> <th>UK</th> <th>US</th> <th>CN</th> <th>AU</th> <th>EU</th> </tr> </thead> <tbody> <tr> <td>S012017</td> <td>S012006</td> <td>S012007</td> <td>S012008</td> <td>S012009</td> <td>S012010</td> </tr> </tbody> </table>	Global*	UK	US	CN	AU	EU	S012017	S012006	S012007	S012008	S012009	S012010	
Global*	UK	US	CN	AU	EU									
S012017	S012006	S012007	S012008	S012009	S012010									
	<i>*Note: The UK plug, US plug, AU plug, and EU plug are all included in Global version.</i>													
Output Connector	2-pin, with cord end terminal													
Related Products	R1520, R2110, R5020, R2000 Dual, R2010, R2011													

